

1 Scope:

- 1.1 This specification is applicable to lead free and halogen free of RoHS for LRH 4 terminals low-inductance metal alloy low-resistance resistor.
- 1.2 The product is belong to the universal series.

2 Explanation Of Part Numbers:

<u>LRH</u>	<u>3637</u>	-	<u>4</u>	<u>2</u>	<u>R020</u>	<u>F</u>	<u>1</u>

Type	Size (inch)	Number of Terminals	Rated Power	Resistance (4~6 Digits)	Tolerance	Packaging
Low-Inductance Metal Alloy Low-Resistance Resistor	• 3637	4: 4 terminals	<ul style="list-style-type: none"> • 2=2.0W • 3=3.0W 	EX: R0025 = 2.5mΩ R005 = 5mΩ R020 = 20mΩ	B=± 0.1% D=± 0.5% F=± 1.0%	1=1,000pcs

3 Product Specifications:


Type	# of Terminals	Max. Rating Power	Max. Rating Current	Max. Overload Current	T.C.R. (ppm/°C)	Resistance Range (mΩ)	Operating Temperature Range
						B(±0.1%) D(±0.5%) F(±1%)	
LRH3637	4	2W	$I_r = \sqrt{P/R}$	$I_o = \sqrt{5P/R}$	$\leq \pm 50$	2.5 ~ 20	-55~170°C
		3W	I_r : Rating Current (A) P : Rating Power (W) R : R value(Ω)	I_o : Overload Current (A) P : Rating Power (W) R : R value(Ω)	$\leq \pm 50$	2.5 ~ 10	

Written	RD Checked	Approved	QA Signing	Remark	Issue Dep. DATA Center.
				IT'S NOT UNDER CONTROL FOR PDF FILE PLS NOTE THE VERSION STATED..	Series No. 60
Do not copy without permission					

3.1 Power Derating Curve:

Operating Temperature Range : - 55 ~+170 °C

For resistors operated in ambient temperatures 70°C, power rating shall be derated in accordance with the curve below:



3.2 Rating Current:

The following equation may be used to determine the DC (Direct Current) or AC (Alternating Current) currents (RMS, root mean square value) of normal rated power. However, if the result value exceeds the highest current of regulated standards, the highest normal rated power is to be used.

Remark:

$$I = \sqrt{P/R}$$

I=Rating Current(A)
P= Rating Power(W)
R=Resistance(Ω)

Remark


IT'S NOT UNDER CONTROL FOR PDF FILE
PLS NOTE THE VERSION STATED..

Issue Dep. DATA Center.

Do not copy without permission

Series No. **60**

4 Physical Dimensions:



Type	# of Terminals	Maximum Power Rating (Watts)	Resistance Range (mΩ)	Dimensions - in inches (millimeters)					
				L	W	A	B	T	H
LRH3637	4	2	2.5~20	0.360±0.010 (9.14±0.254)	0.370±0.010 (9.40±0.254)	0.059±0.010 (1.50±0.254)	0.039±0.010 (1.00±0.254)	0.091±0.010 (2.31±0.254)	0.047±0.010 (1.20±0.254)
		3	2.5~10						

4.1 Material of Alloy

Type	# of Terminals	Watts	Material	Resistance
LRH3637	4	2.0	Nickel-Chromium-Aluminum Alloy	2.5mΩ ~ 20mΩ
		3.0	Nickel-Chromium Aluminum Alloy	2.5mΩ ~ 10mΩ

Remark

IT'S NOT UNDER CONTROL FOR PDF FILE
PLS NOTE THE VERSION STATED..

Issue Dep.**DATA Center.**

Do not copy without permission

Series No. **60**

RALEC 旺詮	LRH 4-Terminals Series Metal Alloy Low-Resistance Resistor Product Specifications	Document No.	IE-SP-184
		Released Date	2020/08/20
		Page No.	4

5 Reliability Performance:

5.1 Electrical Performance:



Test Item	Conditions of Test	Test Limits									
Temperature Coefficient of Resistance (TCR)	<ul style="list-style-type: none"> TCR (ppm/°C) = $\frac{(R2-R1)}{R1 (T2-T1)} \times 10^6$ R1: resistance of room temperature R2: resistance of 150 °C T1: Room temperature T2: Temperature at 150 °C Refer to JIS C 5201-1 4.8 	Refer to Paragraph 3. general specifications									
Short Time Overload	<p>Applied Overload for 5 seconds and release the load for about 30 minutes, then measure its resistance variance rate. (Overload condition refer to below):</p> <table border="1"> <tr> <td>Type</td> <td># of Terminals</td> <td>Power (W)</td> <td># of rated power</td> </tr> <tr> <td rowspan="2">LRH3637</td> <td rowspan="2">4</td> <td>2.0</td> <td rowspan="2">5 times</td> </tr> <tr> <td>3.0</td> </tr> </table> <p>Refer to JIS C 5201-1 4.13</p>	Type	# of Terminals	Power (W)	# of rated power	LRH3637	4	2.0	5 times	3.0	<p>≤ ±0.5%</p> <p>No evidence of mechanical damage</p>
Type	# of Terminals	Power (W)	# of rated power								
LRH3637	4	2.0	5 times								
		3.0									
Insulation Resistance	<p>Put the resistor in the fixture, add 100 VDC in +, - terminal for 60secs then measured the insulation resistance between electrodes and insulating enclosure or between electrodes and base material.</p> <p>Refer to JIS-C5201-1 4.6</p>	≥ 10 ⁹ Ω									
Dielectric Withstanding Voltage	<p>Applied 500VAC for 1 minute, and Limit surge current 50 mA (max.)</p> <p>Refer to JIS-C5201-1 4.7</p>	No short or burned on the appearance.									

5.2 Mechanical /Constructional Performance:

Test Item	Conditions of Test	Test Limits
Resistance to Solder Heat	<p>The tested resistor be immersed 25 mm/sec into molten solder of 260±5°C for 10±1secs. Then the resistor is left in the room for 1 hour, and measured its resistance variance rate.</p> <p>Refer to JIS-C5201-1 4.18</p>	<p>≤ ±0.5%</p> <p>No evidence of mechanical damage</p>
Solderability	<p>Add flux into tested resistors, immersion into solder bath in temperature 245±5°C for 3±0.5secs.</p> <p>Refer to JIS-C5201-1 4.17</p>	Solder coverage over 95%
Vibration	<p>The resistor shall be mounted by its terminal leads to the supporting terminals on the solid table. The entire frequency range :from 10 Hz to 55 Hz and return to 10 Hz, shall be transferred in 1 min. Amplitude : 1.5mm This motion shall be applied for a period of 4 hours in each 3 mutually perpendicular directions (a total of 12hrs)</p> <p>Refer to JIS-C5201-1 4.22</p>	<p>≤ ±0.5%</p> <p>No evidence of mechanical damage</p>

Remark	IT'S NOT UNDER CONTROL FOR PDF FILE PLS NOTE THE VERSION STATED..	Issue Dep. DATA Center.
	Do not copy without permission	Series No. 60

**LRH 4-Terminals Series Metal Alloy
Low-Resistance Resistor Product
Specifications**

Test Item	Conditions of Test	Test Limits
Joint Strength of Solder	<p>Preconditioning Put tested resistor in the apparatus of PCT, at a temperature of 105°C, humidity of 100% RH, and pressure of 1.22×10⁵ Pa for a duration of 4 hours. Then after left the specimen in a temperature for 2 hours or more. Test method:</p> <p>◎Test item 1 (Adhesion): A static load using a R0.5 scratch tool shall be applied on the core of the component and in the direction of the arrow and held for 10 seconds and under load measured its resistance variance rate. Load:17.7N</p>  <p>Refer to JIS-C5201-1 4.32</p>	<p>Test item 1: (1). ≤ ±0.5% (2). No evidence of mechanical damage. No terminal peeling off.</p> <p>Test item 2: (1). ≤ ±0.5% (2). No evidence of mechanical damage. No terminal peeling off and core body cracked.</p>
	<p>◎Test item 2 (Bending Strength): Solder tested resistor on to PC board add force in the middle down, and under load measured its resistance variance rate. D:2mm</p>  <p>Refer to JIS-C5201-1 4.33</p>	

Remark

IT'S NOT UNDER CONTROL FOR PDF FILE
PLS NOTE THE VERSION STATED..

Issue Dep. DATA Center.

Do not copy without permission

Series No. **60**

**LRH 4-Terminals Series Metal Alloy
Low-Resistance Resistor Product
Specifications**

5.3 Environmental Performance:

Test Item	Conditions of Test	Test Limits										
Low Temperature Exposure (Storage)	Put the tested resistor in chamber under temperature $-55\pm 2^{\circ}\text{C}$ for 1,000 hours. Then leaving the tested resistor in room temperature for 60 minutes, and measure its resistance variance rate. Refer to JIS-C5201-1 4.23.4	$\leq \pm 0.5\%$ No evidence of mechanical damage										
High Temperature Exposure (Storage)	Put tested resistor in chamber under temperature $170\pm 5^{\circ}\text{C}$ for 1,000 hours. Then leaving the tested resistor in room temperature for 60 minutes, and measure its resistance variance rate. Refer to JIS-C5201-1 4.23.2	$\leq \pm 0.5\%$ No evidence of mechanical damage										
Temperature Cycling (Rapid Temperature Change)	Put the tested resistor in the chamber under the temperature cycling which shown in the following table shall be repeated 1,000 times consecutively. Then leaving the tested resistor in the room temperature for 60 minutes, and measure its resistance variance rate. <table border="1" style="margin-left: 20px;"> <thead> <tr> <th colspan="2">Testing Condition</th> </tr> </thead> <tbody> <tr> <td>Lowest Temperature</td> <td>$-55 +0/-10^{\circ}\text{C}$</td> </tr> <tr> <td>Highest Temperature</td> <td>$150 +10/0^{\circ}\text{C}$</td> </tr> </tbody> </table> Refer to JIS-C5201-1 4.19	Testing Condition		Lowest Temperature	$-55 +0/-10^{\circ}\text{C}$	Highest Temperature	$150 +10/0^{\circ}\text{C}$	$\leq \pm 0.5\%$ No evidence of mechanical damage				
Testing Condition												
Lowest Temperature	$-55 +0/-10^{\circ}\text{C}$											
Highest Temperature	$150 +10/0^{\circ}\text{C}$											
Moisture Resistance (Climatic Sequence)	Put the tested resistor in chamber and subject to 10 cycles of damp heat and without power. Each one of which consists of the steps 1 to 7 (Figure 1). Then leaving the tested resistor in room temperature for 24 hr, and measure its resistance variance rate. Refer to MIL-STD 202 Method 106	$\leq \pm 0.5\%$ No evidence of mechanical damage										
Bias Humidity	Put the tested resistor in chamber under $85\pm 5^{\circ}\text{C}$ and $85\pm 5\% \text{RH}$ with 10% bias and load the rated current for 90 minutes on, 30 minutes off, total 1,000 hours. Then leaving the tested resistor in room temperature for 60 minutes, and measure its resistance variance rate. Refer to JIS-C5201-1 4.24	$\leq \pm 0.5\%$ No evidence of mechanical damage										
Whisker Test	<p>◎ Test item (Thermal Shock test):</p> <table border="1" style="margin-left: 20px;"> <thead> <tr> <th colspan="2">Testing Condition</th> </tr> </thead> <tbody> <tr> <td>Minimum storage temperature</td> <td>$-55+0/-10^{\circ}\text{C}$</td> </tr> <tr> <td>Maximum storage temperature</td> <td>$85+10/0^{\circ}\text{C}$</td> </tr> <tr> <td>Temperature-retaining time</td> <td>10 min.</td> </tr> <tr> <td>Number of temperature cycles</td> <td>1,500</td> </tr> </tbody> </table> <p>◎ Inspection: Inspect for whisker formation on specimens that underwent the acceleration test specified in subclause 4.2, with a magnifier (stereo microscope) of about 40 or higher magnification. If judgment is hard in this method, use a scanning electron microscope (SEM) of about 1,000 or higher magnification. By JESD Standard NO.22A121 class 2.</p>	Testing Condition		Minimum storage temperature	$-55+0/-10^{\circ}\text{C}$	Maximum storage temperature	$85+10/0^{\circ}\text{C}$	Temperature-retaining time	10 min.	Number of temperature cycles	1,500	Max. $50 \mu\text{m}$
Testing Condition												
Minimum storage temperature	$-55+0/-10^{\circ}\text{C}$											
Maximum storage temperature	$85+10/0^{\circ}\text{C}$											
Temperature-retaining time	10 min.											
Number of temperature cycles	1,500											

Remark

IT'S NOT UNDER CONTROL FOR PDF FILE
PLS NOTE THE VERSION STATED..


Do not copy without permission

Issue Dep. DATA Center.

Series No. **60**

5.4 Operational Life Endurance:

Test Item	Conditions of Test	Test Limits
Load Life	Put the tested resistor in chamber under temperature $70 \pm 2^\circ\text{C}$ and load the rated current for 90 minutes on 30 minutes off, total 1000 hours. Then leaving the tested resistor in room temperature for 60 minutes, and measure its resistance variance rate. Refer to JIS-C5201-1 4.25	$\leq \pm 1.0\%$ No evidence of mechanical damage



6 Measurement Point :

Bottom electrode	Unit : mm		
Type	DIM	A	B
<p>● Current Terminal ⊖ Voltage Terminal</p>	LRH3637-4T	5.10 ± 0.10	6.82 ± 0.10

Remark

IT'S NOT UNDER CONTROL FOR PDF FILE
PLS NOTE THE VERSION STATED..


Issue Dep. DATA Center.

Do not copy without permission

Series No. **60**

7 Taping specifications:

7.1 Tape Dimensions:




Unit: mm

Item	DIM	Ao	Bo	W	E	F	Ko	Po	P1	P2	Do	D1
LRH3637-4		9.6±0.1	9.9±0.1	16.0±0.2	1.75±0.1	7.5±0.1	1.5 Max	4.0±0.1	12.0±0.1	2.0±0.1	1.5±0.1	1.5 Max

7.2 Packaging model:

Type	# of Terminals	Tape width	Max. Packaging Quantity (pcs/reel)
			Embossed Plastic Type
			4mm pitch
LRH3637	4	16mm	1000

7.3 Reel Dimensions:



Reel Type / Tape	W	M	A	D
7" reel for 16 mm tape	17.4 ± 1.0	178 ± 2.0	13.2 ± 0.5	60.0 ± 1.0

Remark



IT'S NOT UNDER CONTROL FOR PDF FILE
PLS NOTE THE VERSION STATED..

Issue Dep. DATA Center.

Do not copy without permission

Series No. **60**


7.4 Label:




8 Technical application note (This is for recommendation, please customer perform adjustment according to actual application)

8.1 Recommend soldering method:

8.1.1 Typical examples of soldering processes that provides reliable joints without any damage are given in below:



Recommended IR Reflow Soldering Profile



Recommended double-wave Soldering Profile

Typical values (solid line)

Process limits (dotted line)

8.1.2 Soldering Iron: temperature $350^{\circ}\text{C} \pm 10^{\circ}\text{C}$, dwell time shall be less than 3 sec.

Remark

IT'S NOT UNDER CONTROL FOR PDF FILE
PLS NOTE THE VERSION STATED..


Issue Dep. DATA Center.

Do not copy without permission

Series No. **60**

8.2 Recommend Land Pattern:

When a component is soldered, the resistance after soldering changes slightly depending on the size of the soldering area and the amount of soldering. When designing a circuit, it is necessary to consider the effect of a decrease or increase in its resistance



Type	# of Terminals	Maximum Power Rating (Watts)	Resistance Range (mΩ)	Dimensions - in millimeters				
				a	b	c	d	i
LRH3637	4	2	2.5 ~ 20	2.95	9.90	1.68	0.60	4.50
		3	2.5 ~ 10					

8.3 Environment Precautions:

This specification product is for general electronic use, RALEC will not be responsible for any damage, cost or loss caused by using this specification product in any special environment. If other applications need to confirm with RALEC.

If consumer intends to use our Company product in special environment or condition (including but not limited to those mentioned below), then will need to make individual recognition of product features and reliability accordingly.

- (a) Used in high temperature and humidity environment
- (b) Exposed to sea breeze or other corrosive gas, such as Cl₂、H₂S、NH₃、SO₂ and NO₂.
- (c) Used in non-verified liquids including water, oil, chemical and organic solvents.
- (d) Using non-verified resin or other coating material to seal or coat our Company product.
- (e) After soldering, it is necessary to use water-soluble detergents to clean residual solder fluxes, even though no-clean fluxes are recommended.

8.4 Momentary Overload Precautions:

The product might be out of function when momentary overloaded. Please make sure to avoid momentary overloading while using and preserving。

Remark

IT'S NOT UNDER CONTROL FOR PDF FILE
PLS NOTE THE VERSION STATED..

Issue Dep.**DATA Center.**

Do not copy without permission

Series No. **60**

RALEC 旺詮	LRH 4-Terminals Series Metal Alloy Low-Resistance Resistor Product Specifications	Document No.	IE-SP-184
		Released Date	2020/08/20
		Page No.	11

8.5 Operation and Processing Precautions:

- (a) Avoid damage to the edge of resistor and protective layer caused by mechanical stress.
- (b) Handle with care when printing circuit board (PCB) is divided or fixed on support body, because bending of printing circuit board (PCB) mounting will make mechanical stress for resistors.
- (c) Make sure the power rating is under the limit when using the resistor. When power rating is over the limit, the resistor will be overloaded. There might be machinery damage due to the climbing temperature.
- (d) If the resistor will be exposed under massive impact load (shock wave) in a short period of time, the working environment must be set up well before use.
- (e) Please make evaluation and confirmation when the product is well used in your company and have a through consideration of it's fail-safe design to ensure the system safety.

9 Storage and transportation requirement:

- 9.1 The temperature condition must be controlled at $25\pm 5^{\circ}\text{C}$, the R.H. must be controlled at $60\pm 15\%$. The stock can maintain quality level in two years ◦
- 9.2 Please avoid the mentioned harsh environment below when storing to ensure product performance and its' weldability. Places exposed to sea breeze or other corrosive gas, such as Cl_2 、 H_2S 、 NH_3 、 SO_2 and NO_2 .
- 9.3 When the product is moved and stored, please ensure the correct orientation of the box. Do not drop or squeeze the box. Otherwise, the electrode or the body of the product may be damaged.

10 Inductance

Inductance characteristics: $< 5\text{nH}$ (Circuit frequency is below 1MHz)

11 Attachments

11.1 Document Revise Record (QA-QR-027)

Remark	IT'S NOT UNDER CONTROL FOR PDF FILE PLS NOTE THE VERSION STATED..	Issue Dep. DATA Center.
	Do not copy without permission	Series No. 60

RALEC 旺詮	LRH 4-Terminals Series Metal Alloy Low-Resistance Resistor Product Specifications	Document No.	IE-SP-184
		Released Date	2020/08/20
		Page No.	12

Legal disclaimer

RALEC, its distributors and agents (collectively, "RALEC"), hereby disclaims any and all liabilities for any errors, inaccuracies or incompleteness contained in any product related information, including but not limited to product specifications, datasheets, pictures and/or graphics. RALEC may make changes, modifications and/or improvements to product related information at any time and without notice.

RALEC makes no representation, warranty, and/or guarantee about the fitness of its products for any particular purpose or the continuing production of any of its products. To the maximum extent permitted by law, RALEC disclaims (i) any and all liability arising out of the application or use of any RALEC product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for a particular purpose, non-infringement and merchantability.

RALEC defined this product is for general electrical use , not design for any application for automotive electrical ,life-saving or life support equipment, or any application which may inflict casualties if RALEC product failure occurred. When consumer is using or selling products of RALEC without having discussion with the sales representatives and specifically stated the applicability mentioned above in a written form, then the client need to take a full responsibility and agree to protect RALEC from punishment and damage.

Information provided here is intended to indicate product specifications only. RALEC reserves all the rights for revising this content without further notification, as long as products are unchanged. Any product change will be announced by ECN.

Remark	IT'S NOT UNDER CONTROL FOR PDF FILE PLS NOTE THE VERSION STATED..	Issue Dep. DATA Center.
	Do not copy without permission	Series No. 60