

UG2A thru UG2D

Glass Passivated Junction Ultra Fast Rectifiers

Reverse Voltage 50 to 200V Forward Current 2.0A

FEATURES

- * Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- * High temperature metallurgically bonded construction
- * Glass passivated chip
- * Capable of meeting environmental standards of MIL-S-1950
- * For use in high frequency rectifier circuits
- * Fast switching for high efficiency
- * High temperature soldering guaranteed: 260°C/10 seconds
- * 0.375" (9.5mm) lead length, 5 lbs. (2.3kg) tension

Mechanical Data

Case: JEDEC DO-15, molded plastic body


Terminals: Plated axial leads, solderable per MIL-STD-750, Method 2026

Polarity: Color band denotes cathode end

Mounting Position: Any

Weight: 0.015 oz., 0.40 g

Handling precaution: None



We declare that the material of product compliance with ROHS requirements

1.Electrical Characteristic

Maximum& Thermal Characteristics Ratings at 25°C ambient temperature unless otherwise specified.

Parameter Symbol	symbol	UG2A	UG2B	UG2C	UG2D	Unit
Maximum repetitive peak reverse voltage	V _{RRM}	50	100	150	200	V
Maximum RSM voltage	V _{RSM}	35	70	105	140	V
Maximum DC blocking voltage	V _{DC}	50	100	150	200	V
Maximum average forward rectified current 0.375" (9.5mm) lead length at T _A = 55°C	I _{F(AV)}			2.0		A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I _{FSM}			65		A
Maximum full load reverse current, full cycle average,0.375"(9.5mm) lead lengths at T _A = 75°C	I _{R(AV)}			100		μA
Typical thermal resistance (Note 2)	R _{θJA}			45		°C/W
Operating junction and storage temperature range	T _J , T _{STG}			-50 to +150		°C

Electrical Characteristics Ratings at 25°C ambient temperature unless otherwise specified.

Parameter Symbol	symbol	UG2A	UG2B	UG2C	UG2D	Unit
Maximum Instantaneous Forward Voltage (IF = 2.0 Amps, T _J = 25°C)	V _F			0.95		V
Maximum full load reverse current, full cycle average,0.375"(9.5mm) lead lengths (Rated dc Voltage, T _J = 100°C) (Rated dc Voltage, T _J = 25°C)	I _R			200		μA
Maximum reverse recovery time (Note 1)	T _{rr}			5.0		
Typical junction capacitance at 4.0V, 1MHz	C _J			15		PF

NOTES:

1. IF = 0.5A, IR = 1.0A, IRR = 0.25A

2. Thermal resistance from junction to ambient at 0.375" (9.5mm) lead length, P.C.B. mounted

UG2A thru UG2D

2. Ratings and Characteristic Curves (TA = 25°C unless otherwise noted)

Fig. 1 - Forward Current Derating Curve




Fig 3. - Typical Instantaneous Forward Characteristics




Fig 5. - typical transient thermal impedance




Fig. 2 - Maximum Non-repetitive Peak Forward Surge Current




Fig 4. - Typical Reverse Characteristics






Fig 6. - Typical Junction Capacitance



UG2A thru UG2D

3. dimension:

Package outline




Dimensions				Note: DO-15 molded plastic case The marking band indicates the cathode	
inches		mm			
	Min.	Max.	Min.	Max.	
L	0.230	0.300	5.8	7.6	
L1	1.0	-	25.4	-	
ΦD	0.104	0.140	2.6	3.6	
Φd	0.028	0.034	0.7	0.9	

标题:	文件编号: WI-250
塑封生产线轴向产品包装规范	第 4 版 第 0 次修改
	第 1 页

1 弹带盒装 ammo and box


1.1. 弹带盒规格 ammo spec.



单位: mm

	L	W	H
T52	262±2	76±2	90±2
T42	262±2	64±2	90±2
T26	250±3	45±3	95±3

1.2 弹带内盒要求 inner box spec.



标题:	塑封生产线轴向产品包装规范	文件编号: WI-250
		第 4 版 第 0 次修改
		第 2 页

1.4 标签要求 label spec.


1.4.1 LRC标签 LRC label

成 型	*****	成型规格 forming spec.
FORMING		
型 号	*****	LRC产品型号 type
TYPE		
重复峰压 (V) PRV (V)	****	产品重复峰压值 peak repetitive voltage
额定电流 (A) I _o (A)	**	产品额定电流值 average output current
数量 (只) Q'TY (pcs) <i>QC单</i>	****	产品数量 quantity
检验员 CHECKER	02	
日期: DATE:	*****	产品生产日期 date

1.4.2 环保标签 environmental protection label



2. 外箱规格 cartoon spec.




3 按以上包装方式，编带数量和外包装箱产品数量: typing and cartoon spec.

	塑封外型			
	A-405 & DO-41 & R-1	R-3	DO-15	DO-201AD
每根编带数量 quantity/ammo	3K	1.8K	2K(T52) 1.8K(T26)	0.8K
外箱数量 (T52编带) quantity/cartoon	30K	18K	20K	8.0K
外箱数量 (T26编带) quantity/cartoon	60K	36K	36K	-
外箱数量 (T42编带) quantity/cartoon	54K	32.4K	36K	-

标题:	文件编号: WI-250
塑封生产线轴向产品包装规范	第 4 版 第 0 次修改
	第 3 页

4 编带规格 brede spec



尺寸代号	编带尺寸 typing dimension					
	26/tape	35/tape	40/tape	42/tape	52/tape	52/tape#
W	26 0.0/+1.6	35 -1.0/+0.5	40 -1.0/+0.5	42 -1.0/+1.0	52 -1.0/+2.0	52 -1.0/+2.0
P	5±0.5	5±0.5	5±0.5	5±0.5	5±0.5	10±0.5
L1-L2	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
H	6±1.0	6±1.0	6±1.0	6±1.0	6±1.0	6±1.0
Z	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
R	<1.0	<1.0	<1.0	<1.0	<1.0	<1.0
T	>3.5	>3.5	>3.5	>3.5	>3.5	>3.5

注: 52编带# 为DO-201AD编带规格 "52编带#" just for D0-201AD

1. 红白编带厚度为0.05mm; 两种胶带各自之间无明显色差; 编带要求均为胶带。

The typing thickness is 0.05mm and color is obvious difference

2. 两端引带20~40cm. Typing lead over 20~40cm

3. 红色编带一端为二极管“负极” ; 白色编带一端为二极管“正极”。

red color is cathode ,white color is anode

4. 无卤 green epoxy compound (无卤产品才贴HF only)


 Green



UG2A thru UG2D

4、版式次更新记录

版次	更新记录	更新作者	更新日期
1	第一版	周杰	2010-6-11
2	修正正向浪涌为65A	周杰	2011.03.29
3	增加包装规范	周杰	2012.03.28